



*Front LCD Console (keyboard, mouse, monitor 17") + KVM Module design(1/4/8/16ports); It's very flexible and convenient for combination;
 *IP optional (IP card could be installed inside KVM module);
 *Extra prepositive USB mouse interface;
 *Single port length: 462.6mm; Multi-ports length: 611mm

17" LCD Console Specification

Type	17" LCD Console	
LCD Monitor	Ratio	17" Screen, 4:3
	Video	SXGA TFT-LCD
	Visible Square	337.920(H) × 270.336(V)
	Resolution (Max)	1920*1080@60HZ
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	Contrast	1000 : 1 (Typ)
	Back light	LED
	Pixel Pitch	0.264x0.297mm
	LED MTBF	100,000 hours
	Input power	12V
Keyboard	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible IBM/AT	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 Times

KVM Module Specification

Type	4 Port			8 Port			16 Port				
Model	AS-7104ULS			AS-7108ULS			AS-7116ULS				
Computer Connection	Direct Connects		4			8			16		
	Maximum Connects		64			128			256		
CPU Port Selection		OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional)									
Connectors	Console Connector	Monitor	17" LED Monitor								
		Keyboard	1 x USB Type A Female								
		Mouse	1 x USB Type A Female								
		Expansion Interface	1 x USB Type A Female (Front expansion Keyboard, Mouse Interface)								
	PC Connector	Monitor, Keyboard/Mouse Switch Module	4 x VGA DB15, Female Blue			8 x VGA DB15, Female Blue			16 x VGA DB15, Female Blue		
		Power	1 x DC Jack								
Network Port		1 x RJ45									
Toggle Switch	Connection Port Selection		KVM Operation Panel Digital keys								
	KVM Reset		KVM Operation Panel Function Keys								
	IP Module Reset		1 x semi-embedded key								
	IP Module Default		1 x semi-embedded key								
LED's	Selected		Nixie Tube Display								
	Online		4 x Red			8 x Red			16 x Red		
	IP Network		1 x Green, 1 x Orange								
Analog Mode	Keyboard/Mouse		USB, PS/2								
Resolution (Max)		1920 x 1200 @ 60HZ Local & Remote									
Scan time interval		3, 5, 10, 15, 20, 30, 40, 60s (3s by default)									
Operating Environment	Operating temperature		-10-50°C								
	Storage temperature		-20-60°C								
	Humidity		0-80%RH, No Condensation								
Physical Properties	Housing		Metal								
	Slide Rail Dimension		555 x 445 x 45 mm								
	Weight		16.6KG-18.1KG								