



- *Front LCD Console (keyboard, mouse, monitor 19") + KVM Module design(1/4/8/16ports); It's very flexible and convenient for combination;
- *IP optional (IP card could be installed inside KVM module);
- *Extra prepositive USB mouse interface;
- *Single port length: 462.6mm; Multi-ports length: 611mm

19" LCD Console Specification



Type		19" Wide-Screen LCD Console
LCD Monitor	Ratio	19" Screen, 16:9
	Video	Wide AHVA TFT-LCD
	Visible Square	408.96(H) x 230.04(V)
	Resolution (Max)	1920*1080@60HZ
	Support Color	16.7M, True 8 bit
	Contrast	1000 : 1 (Typ)
	Backlight	LED
	Pixel Pitch	300*300um
	LEDMTBF	100,000 hours
	Input power	12V
Keyboard	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible IBM/AT	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 Times

KVM Module Specification

Type		4 Port	8 Port	16 Port
Model		AS-9104ULS	AS-9108ULS	AS-9116ULS
Computer Connection	Direct Connects	4	8	16
	Maximum Connects	64	128	256
CPU Port Selection		OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional)		
Connectors	Console Connector	Monitor	19" Wide-Screen LED Monitor	
		Keyboard	1 x USB Type A Female	
		Mouse	1 x USB Type A Female	
		Expansion Interface	1 x USB Type A Female (Front expansion Keyboard, Mouse Interface)	
	PC Connector	Monitor, Keyboard/Mouse Switch Module	4 x VGA DB15, Female Blue	8 x VGA DB15, Female Blue
	Power	1 x DC Jack		
	Network Port	1 x RJ45		
Toggle Switch	Connection Port Selection		KVM Operation Panel Digital keys	
	KVM Reset		KVM Operation Panel Function Keys	
	IP Module Reset		1 x semi-embedded key	
	IP Module Default		1 x semi-embedded key	
LED's	Selected		Nixie Tube Display	
	Online	4 x Red	8 x Red	16 x Red
	IP Network	1 x Green, 1 x Orange		
Analog Mode	Keyboard/Mouse		USB, PS/2	
Resolution (Max)		1920 x 1200 @ 60HZ Local & Remote		
Scan time interval		3, 5, 10, 15, 20, 30, 40, 60s (3s by default)		
Operating Environment	Operating temperature		-10-50°C	
	Storage temperature		-20-60°C	
	Humidity		0-80%RH, No Condensation	
Physical Properties	Housing		Metal	
	Slide Rail Dimension		555 x 445 x 45 mm	
	Weight		16.6KG-18.1KG	